


## AH-108, AH-16TN, AH-32TN


For Intercom, Paging, and Paging/Talkback Systems

**AH-108****FEATURES:**

- 8  $\Omega$ , 10W horn with built-in non-polarized capacitor
  - All metal weather proof construction for indoor or outdoor use
  - Universal swivel mount base
  - Beige baked enamel finish
- **Use with Mid-power (MP-S) system for two-way communication**

**SPECIFICATIONS:**


Power Handling Capacity: 10 Watts (continuous)  
 Impedance: 8  $\Omega$   
 Frequency Response: 300-10,000 Hz  
 Dispersion Angle: 120°  
 Sound Pressure Level: 110 dB at rated output measured 4' on axis  
 Sensitivity as Microphone: -26 dBM  
 (Re: 10 dynes/cm<sup>2</sup>)  
 Dimensions: 6-1/8" bell x 6-1/2" depth

**AH-16TN****FEATURES:**

- Built-in 70V transformer, providing 1, 2, 4, 8, and 16 Watt taps, + 8 $\Omega$  direct
  - High intelligibility, used for paging into large or high noise areas
  - All metal weather proof construction designed for outdoor use
  - Screwdriver selectable wattage taps
  - Universal locking swivel mount
  - Beige baked enamel finish
- **8  $\Omega$  for use with High Power (AP-M) system for two-way communication**

**SPECIFICATIONS:**

Power Handling Capacity: 16 Watts (continuous)  
 Impedance: 8  $\Omega$  direct, 25V or 70.7V transformer  
 Wattage taps: 70.7V: 1/2/4/8/16 W  
 25V: 0.5/1/2/4/8 W  
 Frequency Response: 350-15,000 Hz  
 Dispersion Angle: 130°  
 Sound Pressure Level: 119 dB at rated output measured 4' on axis  
 Sensitivity as Microphone: -28 dBM  
 (Re: 10 dynes/cm<sup>2</sup>)  
 Dimensions: 8-1/8" bell x 9" depth

**AH-32TN****FEATURES:**

- Built-in 70V transformer, providing 2, 4, 8, 16, and 32 Watt taps
  - High intelligibility, used for high-power paging into loud areas or outdoor areas
  - All metal weather proof construction designed for outdoor use
  - Screwdriver selectable wattage taps
  - Universal locking swivel mount
  - Beige baked enamel finish
- **Use with 70V paging systems.**

**SPECIFICATIONS:**

Power Handling Capacity: 32 Watts (continuous)  
 Impedance: 8  $\Omega$  direct, 25V or 70.7V transformer  
 Wattage taps: 70.7V: 1/2/4/8/16 W  
 25V: 0.5/1/2/4/8 W  
 Frequency Response: 325-15,000 Hz  
 Dispersion Angle: 130°  
 Sound Pressure Level: 124 dB at rated output measured 4' on axis  
 Sensitivity as Microphone: -28 dBM  
 (Re: 10 dynes/cm<sup>2</sup>)  
 Dimensions: 8-1/8" bell x 9" depth

Aiphone Corporation  
 1700 - 130th Ave. N.E.  
 Bellevue, WA 98005  
 (206) 455-0510  
 FAX: (206) 455-0071

Communication systems for business, home and industry.

**TOLL FREE TECHNICAL DEPARTMENT**  
**FAX LINE: (800) 832-3765**