

AC-PROX-1G

1-Gang and Mullion-Mount Proximity Reader

The AC-PROX-1G is a 125kHz Wiegand proximity reader designed for single-gang and mullion mounting.

Clamshell cards can be read up to 6" away under ideal conditions.

The frame features horizontal and vertical mounting slots, which allow the reader to be adjusted and leveled.



<p>Power Input 5~14V DC</p> <p>Power Draw 45mA</p> <p>Frequency 125kHz</p> <p>Certifications CSA, FCC, CE, C-Tick</p> <p>UL Listings UL 294/ULC S319-05</p> <p>Operating Temp -40°~149°F (-40°~65°C)</p> <p>Dimensions 1-bang bracket: 5-3/4" H x 2-7/8" W x 7/8" D Mullion: 4-7/16" H x 1-5/8" W x 3/4" D</p>	<p>Supported card formats with AC Nio™</p> <p>26-Bit HID 26-bit (industry standard)</p> <p>32-Bit Kantech, CSN, CSN Type 2</p> <p>33-Bit DSX</p> <p>34-Bit HID Standard, HID C10001, HID 0009P, Honeywell FS42, HID N10002</p> <p>35-Bit XceedID</p> <p>36-Bit Keyscan Indala, Verex G-Prox, Continental</p>	<p>37-Bit XceedID, Fairways, Indala, Honeywell, Interlogix, STid 37-V FS01, Interlogix - XceedID</p> <p>39-Bit Kantech XSF</p> <p>40-Bit Aiphone 40-bit</p> <p>48-Bit HID H2004604</p> <p>50-Bit RBH</p> <p>75-Bit Common access card</p>
---	---	---