



DESCRIPTION

The AC-10K-M is a combination 125 kHz Wiegand proximity reader and security keypad designed to be mounted on a mullion. Clamshell cards can be read up to 6" away under ideal conditions. The keypad allows users to enter pin codes for entry, either on their own or in conjunction with a card swipe.

The following card formats are supported when used with AC Nio™ software:

26-Bit	HID 26-bit (Industry Standard)
32-Bit	Kantech, CSN, CSN Type 2
33-Bit	DSX
34-Bit	HID Standard, HID C10001, HID 0009P, Honeywell FS42, HID N10002
35-Bit	XceedID
36-Bit	Keyscan Indala, Verex G-Prox, Continental
37-Bit	XceedID, Fairways, Indala, Honeywell, Interlogix, STid 37-V FS01, Interlogix - XceedID
39-Bit	Kantech XSF
40-Bit	Aiphone 40-bit
48-Bit	HID H2004604
50-Bit	RBH
75-Bit	Common Access Card

SPECIFICATIONS

Power Input:	5~14V DC
Power Draw:	50mA typical, 115mA peak
Frequency:	125 kHz
Certifications:	CSA, FCC, CE, C-Tick
UL Listings:	UL 294
Operating Temp:	-40°~149°F (-40°~65°C)
Dimensions:	6-1/8" H x 1-3/4" W x 15/16" D