



## WIRING DIAGRAM Central exchange unit Suffix Symbo I Function RJ-45 AX-DVF-P AX-084C, AX-248C, or AX-320C Video door station CN1 V1 Camera equilibrium video 4: blue V1 AX-DVF-P Door station ٧2 5: white/blue ٧2 Camera equilibrium video terminal block D1 Е Doorphone -6: green Е CN1: D1 ~ D8 CN2: D9 ~ D16 CN3: D17 ~ D24 CN4: D25 ~ D32 $(\sim 32)$ RJ-45 CAT5e Е Doorphone -3: white green Е VP1 VP1 Camera power supply + 2: orange VP2 VP2 Camera power supply -1: white orange D 8: brown D Doorphone + 300m D Doorphone + 7: white brown D

## IMAGE VIEW AREA & MOUNTING HEIGHT



Camera angle straight forward position







\* The figures are approximate.

## RESTRICTIONS


Do not have rain escape openings on bottom covered with caulking seals. AX-DVF-P door station is exclusively used for AX System. Avoid installing AX-DVF-P door station in the following locations;



At the entrance where background is sky in upper floors of building, etc.



The background of the standing caller's is white wall.



Where the standing location is strongly sunlit.

## FUNCTIONS

Initiating a call to and entering communication with Master station It can ring multiple Master stations (programmable) Directory card is backlit constantly

DESCRIPTION	FIG. NAME		UNIT	DATE
COLOR VIDEO DOOR STATION (AX)	WIRING/IMAGE/RESTR./FCN.		mm	12 April, 2006
MODEL NO.	FIG.NO.	PAGE	REVISION	AIRNANP
AX-DVF-P	41557-2-2	2/2	1	AIPHONE