

#### DESCRIPTION:

The IS-DVF-2RA-FR is a stainless steel flush mount video door station with standard and emergency call buttons. The unit is equipped with French signage for both the standard and emergency buttons. A call status indicator is included to meet rescue assistance requirements.

The emergency button will trigger two programmable relay outputs for activation of external systems or devices.

The built-in camera provides a 170° viewing angle, and can be adjusted digitally for pan, tilt, and zoom views of the entry area. A directory strip for location identification is also provided. The unit is made of stainless steel and includes tamper resistant screws.

The IS-DVF-2RA-FR is compatible with the IS Series communication system. Wiring is CAT-5e or CAT-6 to the designated exchange unit (IS-CCU or IS-SCU). Flush mount with the supplied back box or surface mount with the SBX-IDVFRA.

#### FEATURES:

- Audio communication and visual identification of calling area
- Two call buttons: Standard and Emergency
- LED call status indicator
- Red mushroom button for emergency call
- Directory strip
- Stainless steel faceplate with tamper resistant screws



# IS-DVF-2RA-FR

Stainless Steel Video Emergency Call Station with French Language Signage

## FEATURE CALL-OUT DEFINITIONS:

- [1] Camera
- [2] Microphone
- [3] White LED illuminator
- [4] Speaker
- [5] Directory card
- [6] Call status indicator
- [7] Appel signage
- [8] Call button
- [9] Emergency button
- [10] Urgence signage

## SPECIFICATIONS:

- Power Source: 48VDC (supplied from CEU)
- Communication: Open voice hands-free
- Camera: 1/4" color CMOS
- Min. illumination: 5 Lux
- Wiring: CAT-5e or CAT-6
- Wiring distance: 980'
- Door release: 24V AC/DC, 500mA  
(N/O, COM, N/C)
- Operating Temp: 14° - 140°F (-10° - 60°C)
- Dimensions: 11-<sup>11</sup>/<sub>16</sub>" H x 7" W x 1-<sup>7</sup>/<sub>8</sub>" D

## FEATURE CALL-OUTS:

