

DESCRIPTION:

The IX-DF-HID is an IP addressable video door station for the IX Series, with a built in HID® ProxPoint® Plus card reader.

The video door station will connect via CAT-5e/CAT-6 wire to a local area network (LAN). Maximum wire distance from the door station to the LAN is 330' (standard network wire distance rules apply).

Wiring and power for the card reader are separate from the intercom wiring. The card reader is to be connected to a host controller of any type that is compatible with the HID® ProxPoint® Plus proximity card reader.

Flush mount with the supplied back box or surface mount with the SBX-ISDVF.

FEATURES:

- IP Video door station for IX Series
- Stainless steel faceplate
- Visual call indication lights
- HID® ProxPoint® Plus proximity card reader built in
- Tamper resistant screws
- ONVIF Profile S compliant



IX-DF-HID

IP Addressable Flush Mount Video Door Station with HID® ProxPoint® Plus Card Reader

FEATURE CALL-OUT DEFINITIONS:

- [1] Camera
- [2] Microphone
- [3] Status LED's
- [4] Speaker
- [5] Call button
- [6] White LED for night viewing
- [7] HID® ProxPoint® Plus proximity reader

SPECIFICATIONS:

- Power Source: 802.3af PoE compliant
- Communication: Open voice hands-free
- Camera: 1/4" color CMOS VGA
- Min. illumination: 5 Lux
- Wiring: CAT-5e or CAT-6
- Door release: 24V AC/DC, 500mA (N/O, COM, N/C)
- Operating Temp: -22° - 140°F (-30° - 60°C)
- Ingress Protection: IP55
- Dimensions: 10-7/16"H x 5-7/8"W x 2"D

FEATURE CALL-OUTS:

