

## IX-EA


### IP Video Door Station

The IX-EA is a surface-mount weather-resistant IP video door station that connects to a network using Cat-5e/6 cable. The station is also SIP compliant.

Equipped with a 1.23 megapixel fixed camera, its angle can be vertically adjusted using a lever on the back of the station. Video can be streamed to third-party devices using ONVIF® Profile S or RTSP. Audio and video can be stored on a microSD™ card.

It can be programmed to call up to 20 stations and one of three different call levels can be selected. The station has a 600Ω output that can be used for paging or communication. One contact output can be programmed to trigger during door release or based on the status of the station. One input that can be used to trigger an outgoing call or answer a call/page.

There are audible and visual indicators for calling, communication, and door release. Sound files can be uploaded for custom messages to be played during door release, call placed, communication start, error message, and more.



- SIP compliant
- PoE (802.3af)
- 1.23 megapixel fixed video camera
- White LED for low light illumination
- ONVIF® Profile S compliant
- Camera vertical adjustment +13°, 0°, or -8° (manual)
- Slot for microSD™ card
- Weather resistant
- One contact output
- One trigger input
- 600Ω audio output

<b>Power Source</b>	PoE (IEEE 802.3af class 0)
<b>Power Draw</b>	5.18W max
<b>Camera</b>	1/3" CMOS 1.23 megapixel
<b>Audio Codec</b>	G.711 (μ-law, A law), G.722
<b>Video Codec</b>	H.264/AVC, motion JPEG
<b>Protocols</b>	IPv4, IPv6, TCP, UDP, SIP, HTTP, HTTPS, RTSP, RTP, RTCP, IGMP, MLD, SMTP, SFTP, DHCP, NTP, DNS
<b>Port Security</b>	IEEE 802.1X
<b>Operating Temp</b>	-40° ~140°F (-40° ~60°C)
<b>Protection</b>	IP54
<b>Dimensions</b>	6-5/16" H x 3-15/16" W x 1-3/4" D