



DESCRIPTION

IX-SOFT is a software answering station for the IX|IXG Series. Use IX-SOFT to call and communicate with IX Series stations across a network. Software answering station features include monitoring, paging, and door release. Check device functionality and network status of each station using the Line Supervision menu. Use the interactive map to quickly interact with door and answering stations by selecting them individually or by dragging to select a group. IX-SOFT requires a single, transferable lifetime license per PC, with bundles available with 3, 5, or 10 IX-SOFT.

FEATURES

- Place and receive calls and pages
- Monitor door stations
- 50 programmable speed-dial buttons
- Call history
- Call transfer
- Interactive map
- Line Supervision
- Certified for use with Cisco Unified Call Manager®
- Certified for use with Acatel-Lucent's OmniPCX Enterprise™ (OXE) and OXO Connect™ platforms

SPECIFICATIONS

- Video Codec:** H.264/AVC, Motion-JPEG
- Audio Codec:** G.711 (μ-law, A-law), G.722
- Protocol:** IPv4, IPv6, TCP, UDP, SIP, HTTP, HTTPS, RTSP, RTP, RTCP, IGMP, MLD, SMTP, SFTP, DHCP, NTP, DNS
- Encryption:** TLS 1.2 (CRAM-MD5 for email)
- Packet Delivery:** Unicast or Multicast
- Station Capacity:** 499 stations max.
(9,998 max. in expanded mode)
- Video Streaming:** ONVIF® Profile S

SYSTEM REQUIREMENTS

Operating System	Windows® 7 Professional, Windows® 7 Enterprise, Windows® 7 Ultimate Windows® 8.1, Windows® 8.1 Pro, Windows® 8.1 Enterprise Windows® 10 Home, Windows® 10 Pro, Windows® 10 Enterprise, Windows® 10 Education Windows® 11 Home, Windows® 11 Pro, Windows® 11 Enterprise
CPU	32 bit (x86) processor or 64 bit (x64) processor, 2 GHz or higher
Memory	4 GB or higher
Screen Resolution	1280 x 768 or greater
Runtime	.NET Framework 4.6.2 or later (Windows® 7 requires SP1) Microsoft Visual C ++ Redistributable Package for Visual Studio 2017 or later