


IXG-2C7

IP Video Tenant Station

The IXG-2C7 is an IP video tenant station with a 7" LCD touchscreen. It can receive calls from other stations in the system, and call registered guard stations. Communication is hands-free.

Touching the key button will unlock a door or entrance station during communication. Tenants can summon the elevator to their floor with the elevator call button.

A history of received calls is maintained in its built-in memory, which can be expanded by adding a microSD™ card. Up to eight IXG-2C7s can be installed in a single unit. Each can selectively communicate with other IXG-2C7s in the same unit or call the unit's mobile apps.



- **7" touchscreen**
- **Hands-free audio communication**
- **Place calls to other stations within tenant**
- **Call concierge/guard**
- **Call elevator to floor**
- **Monitor door stations**
- **Memory can be expanded with microSD™ card**
- **PoE powered (802.3af)**

Power Source PoE (IEEE 802.3af class 0)

Power Draw 1.9W standby, 5.9W max

Screen 7" LCD TFT touchscreen

Monitor Resolution 800 x 400

Communication Full-duplex

Audio Codec G.711 (μ-law, A-law)

Protocols IPv4, IPv6, TCP, UDP, SIP, HTTP, HTTPS, RTSP, RTP, RTCP, IGMP, MLD, SMTP, SFTP, DHCP, NTP, DNS, TLS

Encryption TLS 1.2

Operating Temp 32°~104°F (0°~40°C)

Dimensions 5-13/16" H x 8-15/16" W x 1" D