DATA SHEET

IXG-MK

IP Video Guard Station

The IXG-MK is an IP video guard station with a 7" LCD touchscreen for the IXG Series multi-tenant system. A guard unit can have up to 8 IXG-MK stations. The IXG-MK station can place or receive calls from other stations in the system. Once the call is answered, communication can be hands-free (VOX) or full duplex (handset).

Touching the key button will unlock a door or entrance station during communication. The IXG-MK can have up to 9,999 units in its address book and it will maintain a history of calls that it has received. A microSD™ card can be added to record calls that are placed to the IXG-MK IP video guard station.



- 7" TFT color LCD touchscreen
- Color video camera with privacy shutter
- 9,999 unit address book
- View ONVIF® Profile S cameras
- Multi-angled desk stand included (30°, 45°, 60°)
- Slot for microSD™ card (not provided by Aiphone)
- PoE (802.3af)
- 2 contact outputs, 4 trigger inputs
- 8Ω 0.5W speaker output
- \bullet 600 Ω audio input

Power Source PoE (802.3af)

Network Interface 10 BASE-T/100 BASE-TX Ethernet (RJ-45)

Protocols IPv4, IPv6, TCP, UDP, SIP

Bandwidth Usage Audio (G.722): 64Kbps x 2 for

communication, 64kbps for monitoring

Video (H.264): 32Kbps-2,048Kbps

Video Stream ONVIF® Profile S

Communication Hands-free (full-duplex), push-to-talk

(simplex), or handset (full-duplex)

Video Display 7" LCD touchscreen

Door Release N/O dry contact, 24V AC/DC, 1A

Mounting Wall or desk mount (stand included)

Wire Type Cat-5e or Cat-6

Distance Master Station to Network Node: 330'

Dimensions 8-1/16" H x 11" W x 2-3/16" D