



## DESCRIPTION

The IXW-PBX is a Grandstream IP PBX that will integrate with IX Series stations, allowing for outside line calling. This adaptor will prove beneficial for applications that need an IX station to call to an outside phone number, but a full IP PBX system is not available or needed.

## FEATURES

- Supports up to 500 registered SIP devices and up to 50 concurrent calls
- Dual Gigabit network ports with integrated PoE+
- Built-in call recording server; recordings accessed via web interface
- Built-in call detail records for tracking phone usage
- Supports any SIP video endpoint
- Supports voice mail
- Supports call queue for call volume management

## SPECIFICATIONS

Power Source:	12V DC, 1.5A (supplied)
Video Codecs:	H.264, H.263, H.263+
Network Interface:	Dual Gigabit with integrated PoE+ (IEEE 802.3at)
PSTN FXO Ports:	2
Protocols:	TCP/UDP/IP, RTP/RTCP, ICMP, ARP, DNS, DDNS, DHCP, NTP, TFTP, SSH, HTTP/HTTPS, PPPoE, SIP, STUN, SRTP, TLS, LDAP
Encryption:	SRTP, TLS, HTTPS, SSH
Operating Temp:	32° ~ 104°F (0° ~ 40°C)
Dimensions:	6-1/8" H x 8-7/8" W x 1-3/8" D