

IXW-PBXA

IP PBX Adaptor

The IXW-PBXA is a Grandstream IP PBX adaptor that integrates with IX|IXG Series stations, allowing the stations to call to an outside telephone line.

This adaptor is intended for sites where IP PBX features are required, but a full or compatible system is not available.



- **Supports up to 500 registered SIP devices and up to 75 concurrent calls**

- **Dual Gigabit network ports with integrated PoE+**

- **Built-in call recording server; recordings can be accessed via web interface**

- **Built-in call detail records for tracking phone usage**

- **Supports any SIP video endpoint**

- **Supports voice mail**

- **Supports call queue for call volume management**

Power Source 12V DC, 1.5A (supplied)

Video Codecs H.264, H.263, H.263+, H.265, VP8

Network Interface Three self-adaptive Gigabit with integrated PoE+ (IEEE 802.3at)

Ports 2 PSTN FXO, 2 analog FXS

Protocols TCP/UDP/IP, RTP/RTCP, ICMP, ARP, DNS, DDNS, DHCP, NTP, TFTP, SSH, HTTP/HTTPS, PPPoE, SIP, STUN, SRTP, TLS, LDAP, HDLC, HDLC-ETH, PPP, IPv6, OpenVPN*

Encryption SRTP, TLS, HTTPS, SSH

Operating Temp 32° ~ 113°F (0° ~ 45°C)

Dimensions 7" H x 10-5/8" W x 1-1/8" D