

SPECIFICATIONS

0. = 0 0						
Power source	Supplied from Master station					
Type of communication	Open voice hands-free communication					
Camera	1/4 inch color CMOS					
Minimum illumination	5 Lux					
Camera angle	Wide: 170° (approx.) (Horizontal)					
Ambient temperature	-10 ~ 60					
Mounting	Surface wall mount (Directly to wall or electrical box)					
Electrical box	Single-gang box					
Housing	Fire-retardant PC + ABS plastic					
Weight	190g (approx.)					
Unit color	Front panel: Shining silver					
OHIT COTO	Unit: Clear Black					
Remarks	Weather-resistant (JIS C 0920 Protection grade 3 equivalent)					
DESCRIPTION (Color,		FIG. NAME		UNIT	DATE	
VIDEO DOOR STATION Vandal-resistant		PRODUCT/SPECIFICATIONS		mm	25 December, 2008	
MODEL NO.		FIG.NO.	PAGE	REVISION	AIBLIANE	
JK-DA		56832-1-3	1/3	1	AIPHONE	

WIRING DIAGRAM AE0.9~1.2-2C Video door Master station station NP (Color monitor) JK-DA A2 100m * *. When sub master station is connected, the distance between door and sub master will be 100m. IMAGE VIEW AREA & MOUNTING HEIGHT Wide Zoom 700mm 1,050mm (approx.) (approx.) 900mm (approx Objects appear smaller due to greater distortion in the surrounding sections compared to the central section, but a wider area is displayed. Image view area depends on the camera zoom position. Wide Vertical Horizontal Mounting height 1,500mm Mounting height 1,300mm -2,000mm (approx.) 1,800mm (approx.) ,050mm . 050mm (approx.) approx.) Unit/ <u>**1**</u>950mm (approx.) Unit -750mm center 2 center (approx.) 1.500mm 1,300mm2 Zoom(Mounting height: 1,500mm) Vertical Zoom <top> Zoom <bottom> Zoom <center> 2,250mm (approx.) 1,850mm 850mm (approx.) (approx.) 1.600mm 700mm (approx.) (approx.) 1,400mm (approx.) 850mm (approx.) Unit/ -1.150mm (approx.) center center 1,500mm -750mm 1,500mm 1.500mm (approx.) Horizontal Zoom < left> Zoom <center> Zoom <right> 500mm 500mm 500mn 100mm 100mm 1,300mm 1,300mm (approx.) (approx. 900mm(approx.) (approx. DESCRIPTION FIG. NAME UNIT DATE (Color, VIDEO DOOR STATION Vandal-resistant) WIRING DIAGRAM/IMAGE 25 December, 2008 mm MODEL NO. FIG.NO. **PAGE REVISION** AIPHONE

56832-2-3


2/3

1


JK-DA

RESTRICTIONS


Do not cover the water escape holes with caulking seals. JK-DA door station is exclusively used with JK Series Master stations. Avoid to install JK-DA in the following locations;



At the Entrance where background is sky in upper floors of Condominiums, etc.



The background of the standing caller's is white wall.



Where the standing location is strongly sunlit.

FUNCTIONS

Initiating a call to and entering communication with Master station The illuminator LED lights up during communication with Master station

DESCRIPTION	(Color,	FIG. NAME		UNIT	DATE
VIDEO DOOR STATION	Vandal-resistant)	RESTRICTIONS/FUN	CTIONS	mm	25 December, 2008
MODEL NO.		FIG.NO.	PAGE	REVISION	AIRHANE
JK-DA		56832-3-3	3/3	1	AIPHONE