

WIRING DIAGRAM






IMAGE VIEW AREA & MOUNTING HEIGHT

Vertical

Camera angle: 0°




Camera angle: +7°




Horizontal 500mm 950mm *

Camera angle: +17 $^{\circ}$



Camera angle: -7 $^{\circ}$ (When the station is at a high position due to a step)



 * The figures are approximate.

DESCRIPTION	FIG. NAME		UNIT	DATE
VIDEO DOOR STATION (Color)	WIRING/IMAGE VIEW AREA		mm	10 June, 2013
MODEL NO.	FIG.NO.	PAGE	REVISION	AIRHANE
JO-DA	59273-2-3	2/3	1	AIPHONE


RESTRICTIONS

Do not cover the drainage holes with caulking seals.


JO-DA door station is exclusively used for JO Series.

JO-DA is mountable on each Angle box: JBW-D & KAW-D.


Avoid installing JO-DA door station in the following locations;



At the entrance where background is sky in upper floors of building, etc.



The background of the standing caller's is white wall.



Where the standing location is strongly sunlit.

FUNCTIONS

Initiating a call to and entering communication with Master monitor station or Expansion monitor station.

White light LED turns on during low-light conditions when monitoring and talking status. Location LED is steadily lit while the Master monitor station or the Expansion monitor station is in powered status.

DESCRIPTION VIDEO DOOR STATION (Color)	FIG. NAME RESTRICTIONS/FUNCTIONS		UNIT mm	DATE 10 June, 2013
MODEL NO.	FIG.NO.	PAGE	REVISION	AIRUANE
JO-DA	59273-3-3	3/3	1	AIPHONE