

JO-DV

Video Door Station

The JO-DV is an zinc die-cast surface-mount video door station that is available in the JOS-1VW box set or sold separately. The station includes a camera, microphone, speaker, call button, low-light LED, backlit nameplate, and tamper-resistant screws for mounting.

It connects to the JO-1MDW answering station, JO-1FD expansion station, or JOW-2D two-door station adaptor up to 330' away using 18 AWG 2-conductor solid core cable.

When the call button on the door station is pushed, the answering and expansion stations will ring and the video from the door station will be displayed. Two-way communication is established when the call is answered.

The JO-DV is also compatible with GT Series GT-MKB-N video guard station.



- **Two-way hands-free communication**
- **White LED automatically turns on in low-light conditions**
- **2-conductor wiring**
- **Backlit nameplate**
- **Sold separately and as part of the JOS-1VW box set**
- **Compatible with the GT-MKB-N video guard station**

Power Source Supplied by the answering station, expansion station, or video guard station

Communication Hands-free

Camera Type: 1/4" CMOS

View Area: 21" vertical x 3'1" horizontal at 20"

Min Illumination 5 lux

Operating Temp -4°~140°F (-20°~60°C)

Material Zinc die-cast

Mounting Surface mount directly to wall

Wire Type 2-conductor, low cap, non-shielded, PE insulation, 18 AWG (use Aiphone #871802)

Distance 330' (18 AWG)

Dimensions 6-13/16" H x 3-7/8" W x 1-1/16" D