

JP-4HD

Video Sub Answering Station

The JP-4HD is a video sub answering station that can be used with the JP-4MED answering station. Up to seven sub answering stations can be used in a JP Series system. It has a 7" LCD touchscreen and allows for handset (duplex) and hands-free (VOX) communication.

This station has a door release button for the user to allow visitor entry. The JP-4HD is also equipped with PTZ camera and brightness controls, giving the user different options to vary the camera angle and camera lighting for better visibility.

The JP-4HD connects to either the JP-4MED answering station or JP-8Z distribution adaptor using Cat-5e/6 cable.



- **7" touchscreen LCD**
- **Hands-free (VOX) or handset communication**
- **Door release**
- **PTZ and brightness control**
- **Eight selectable call tones**
- **Station partitioning**
- **All call to inside stations**
- **Continuous room monitoring**

Power Source	24V DC (use PS-2420UL)		
Power Draw	200mA max		
Dry Contacts	N/O 24V AC/DC, 500mA		
Communication	Hands-free (VOX) or handset (full-duplex)		
Video Display	7" LCD touchscreen		
Resolution	800 x 480		
Mounting	Surface mount directly to wall or 1-gang box or desk mount using MCW-S/B		
Operating Temp	32°F~104°F (0~40°C)		
Dimensions	5 3/4 in H	10 1/16 in W	1 15/16 in D
	145 mm H	255 mm W	48 mm D
Weight	≈1.72lbs (780g)		