

DESCRIPTION:

The JP-DVF-HID is a video door station for the JP Series with a built-in HID® proximity card reader.

The video door station will connect via 18AWG 2 conductor wire to the JP-4MED master station. Maximum distance from the door station to the master station is 330' with 871802 wire (980' with JPW-BA long distance adaptor).

Wiring and power for the card reader are separate from the intercom wiring. The card reader is to be connected to a host controller of any type that is compatible with the HID® ProxPoint® Plus card reader.

Flush mount with supplied back box or surface mount with SBX-IDVFRA.

FEATURES:

- Video door station for JP Series
- Stainless steel faceplate
- Directory strip
- HID® ProxPoint® Plus card reader built-in
- Tamper resistant screws



JP-DVF-HID

Stainless Steel Flush Mount Video Door Station with HID® Proximity Card Reader

FEATURE CALL-OUT DEFINITIONS:

- [1] Camera
- [2] Microphone
- [3] White LED illuminator
- [4] Speaker
- [5] Directory card
- [6] Call button
- [7] Card reader

SPECIFICATIONS:

- Power Source: 24VDC (supplied from JP-4MED master station)
- Communication: Open voice hands-free
- Camera: 1/4" color CMOS
- Min. illumination: 5 Lux
- Wiring: 18AWG 2 conductor
- Wiring distance: 330'
- Operation Temp: -4° - 140°F (-20° - 60°C)
- Dimensions: 11-1/16" H x 7" W x 1-7/8" D

FEATURE CALL-OUTS:

