

DESCRIPTION:

The JP-DVF-RP10 is a video door station for the JP Series with a built-in HID® multiCLASS SE® card reader.

The video door station will connect via 18AWG 2 conductor wire to the JP-4MED master station. Maximum distance from the door station to the master station is 330' with 871802 wire (980' with JPW-BA long distance adaptor).

Wiring and power for the card reader are separate from the intercom wiring. The card reader is to be connected to a host controller of any type that is compatible with the HID® multiCLASS SE® RP10 card reader.

Flush mount with supplied back box or surface mount with SBX-IDVFRA.

FEATURES:

- Video door station for JP Series
- Stainless steel faceplate
- Directory strip
- HID® multiCLASS SE® RP10 card reader built-in
- Tamper resistant screws



JP-DVF-RP10

Stainless Steel Flush Mount Video Door Station with HID® multiCLASS SE® Reader

FEATURE CALL-OUT DEFINITIONS:

- [1] Camera
- [2] Microphone
- [3] White LED illuminator
- [4] Speaker
- [5] Directory card
- [6] Call button
- [7] Card reader

SPECIFICATIONS:

- | | |
|--------------------|--|
| Power Source: | 24VDC (supplied from JP-4MED master station) |
| Communication: | Open voice hands-free |
| Camera: | 1/4" color CMOS |
| Min. illumination: | 5 Lux |
| Wiring: | 18AWG 2 conductor |
| Wiring distance: | 330' |
| Operation Temp: | 14° - 140°F (-10° - 60°C) |
| Dimensions: | 11- ¹ / ₁₆ " H x 7" W x 1- ⁷ / ₈ " D |

FEATURE CALL-OUTS:

