

JP-DV

Video Door Station

The JP-DV is an zinc die-cast surface-mount video door station that is available in the JPS-4AEDV box set or sold separately. The station includes a camera, microphone, speaker, call button, low-light LED, backlit nameplate, and tamper-resistant screws for mounting.

It connects to the JP-4MED answering station up to 330' away using 18AWG 2-conductor solid core cable. This can be extended to 980' with the optional JPW-BA long distance adaptor and 851602 cable.

When the call button on the door station is pushed, the answering stations will ring and the video from the door station will be displayed. Two-way communication is established when the call is answered.



- **PTZ camera**
- **Two-way hands-free communication**
- **White LED automatically turns on in low-light conditions**
- **2-conductor wiring**
- **Backlit nameplate**
- **Vandal resistant**
- **Sold separately and as part of the JPS-1AEDV box set**

Power Source Supplied by the answering station, expansion station, or video guard station

Communication Hands-free

Camera Type: 1/4" CMOS

View Area: 100° vertical x 170° horizontal

Min Illumination 5 lux

Operating Temp 14°~140°F (-10°~60°C)

Material Zinc die-cast

Mounting Surface mount directly to wall

Wire Type 2-conductor, low cap, non-shielded, PE insulation, 18 AWG (use Aiphone #871802)

Distance 330' (18 AWG)

Dimensions 6-13/16" H x 3-7/8" W x 1-1/16" D