

# JV-DVF

## Video Door Station

The JV-DV is a stainless steel flush-mount video door station that is available in the JVS-1F box set. The station includes a camera, microphone, speaker, call button, low-light LED, backlit nameplate, and tamper-proof screws for mounting.

It connects to a JV-1MD video answering station or JV-1FD video expansion station up to 330' away using 2-conductor 18AWG solid core cable.

When the call button on the door station is pushed, the answering and expansion stations will ring and the video from the door station will be displayed. Two-way communication is established when the call is answered.



- **Two-way hands-free communication**
- **White LED automatically turns on in low-light conditions**
- **2-conductor wiring**
- **Vandal-resistant, stainless steel construction**
- **Call button with lit bell icon**

<b>Power Source</b>	Supplied by the answering station or expansion station	<b>Operating Temp</b>	-4°~ 140°F (-20°~ 60°C)
<b>Communication</b>	Hands-free	<b>Material</b>	Stainless Steel
<b>Camera</b>	Type: 1/5" CMOS View Area: 1'9" vertical x 3'1" Horizontal at 20"	<b>IP/IK Rating</b>	IP54, IK08
<b>Min Illumination</b>	5 lux	<b>Mounting</b>	Surface mount directly to wall
<b>Door Release</b>	Door Station Output: N/O dry contact, 24V AC/ DC, 1A Second Door Station Output: N/O wet contact, 500mA or less, 12V DC Door Station Input: request to exit, N/O dry contact	<b>Wire Type</b>	2-conductor, low cap, non-shielded, PE insulation, 18 AWG (use Aiphone #871802)
		<b>Distance</b>	330' (18 AWG)
		<b>Dimensions</b>	8 1/4 in H      5 5/16 in W 209 mm H      135 mm W

The JV-DVF video door station is a component of the JVS-1F box set, which also includes the JV-1MD video answering station and PS-2420UL power supply. The JV-DVF is not sold separately.