

## DATA SHEET


## TW-SE

## **Short Tower**

The TW-SE is an aluminum tower for housing IX|IXG Series emergency stations. Made of lightweight aluminum, the tower is a durable solution for outdoor assistance and emergency call applications.

Equipped with a blue strobe light and reflective EMERGENCY lettering on three sides, the tower is highly discernible in areas such as campuses, parking lots, malls, courtyards, and more.

Compatible emergency stations are the IX-DVF-2RA, IX-DVF-2RA-FR, IX-DVF-RA, IX-DVF-RA-FR, IX-SSA-2RA, IX-SSA-2RA-FR, IX-SSA-RA, and IX-SSA-RA-FR. With the optional TW-SPL adaptor plate, the tower can be used with the IX-DVF and IX-SSA non-emergency call stations. To secure the tower in place, our TW-MKL L-bolt mounting kit is required.



- UL-514-A listed electrical box included at the base
- One access panel is located on the back
- EMERGENCY lettering on left, right, and back sides
- Beacon is always lit and strobes during emergency calls (requires 24V DC)
- Weather and vandal resistant
- LED for station illumination in station overhang (requires 24V DC)
- Call button mounting height and signage meet ADA regulations
- Durable, lightweight aluminum

Material Aluminum 6061-T6

Weight 43 lbs

Dimensions 73" H x 8" W x 8" D